

IPC-A8838W-I250S

4K Network IR PTZ Dome Camera



- زوم اپتیکال تا 38 برابر بزرگ نمایی
- لوکس نوری پایین
- فوکوس دقیق و سریع
- IR هوشمند تا 250 متر
- طلق ضد بازتاب نور مادون قرمز
- سنسور ژيروسکوپ
- رزولوشن 8 مگاپیکسل
- Ultra 256, H.265, H.264, MJPEG
- پشتیبانی از 3 استریم تصویر
- OSD قابل تنظیم

- ### قابلیت های کلیدی
- پشتیبانی از پروتکل ONVIF
 - طراحی موثر دفع گرما
 - تکنولوژی کنترل دمای هوشمند
 - مقاومت در برابر نفوذ آب و گرد و غبار IP66
 - PoE++ (IEEE 802.3bt)

Specifications

sensor	1/1.8", 8.0 megapixel, progressive scan, CMOS				
Lens	5.7 - 216.6mm, AF automatic focusing and motorized zoom lens				
Digital Zoom	16				
Optical Zoom	38				
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	5.7	146.3	58.5	29.3	14.6
DORI Distance	216.6	4545	1818	909	454.5
	61.2° - 2.3°				
Angle of View (V)	36.8° - 1.3°				
Angle of View (O)	75.3° - 2.7°				
Shutter	Auto/Manual; shutter time: 1 - 1/100000s				
Minimum Illumination	Colour: 0.003Lux (F1.5, AGC ON) 0Lux with IR				
Iris	Auto/Manual; F1.5 - F4.8				
Day/Night	IR-cut filter with auto switch (ICR)				
Digital noise reduction	2D/3D DNR				
S/N	>55dB				
IR Range	UP to 250m (820ft)				
Defog	Optical Defog & Digital Defog				
WDR	120dB				
Video Compression	Ultra 265, H.265, H.264, MJPEG				
H.264 code profile	Baseline profile, Main Profile, High Profile				
Frame Rate	Main Stream: 8MP (3840*2160), Max 30fps;				
	Sub Stream: 2MP (1920*1080), Max 30fps;				
	Third Stream: D1 (720*576), Max 30fps				
HLC	Supported				
BLC	Supported				
EIS	Supported (gyroscope)				
OSD	Up to 8 OSDs				
Privacy Mask	Up to 24 areas				
ROI	Up to 8 areas				
Motion Detection	Up to 4 areas				

Smart Features	Audio detection, Cross line, intrusion, enter area, leave area, object left, object removed, Deep learning, Smart intrusion, Prevention, face recognition, video meta data, people counting (Deep learning), Face capture, Auto tracking (Deep learning)
General Function	Watermark, IP Address Filtering, Tampering Alarm, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication
Audio Compression	G.711
Two-way audio	Supported
Suppression	Supported
Sampling Rate	8KHZ
Edge Storage	Micro SD, up to 256GB
Network Storage	ANR
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API
Pan Range	360° (endless)
Pan Speed	0.1°/s - 74°/s Preset speed: 300°/s
Tilt Range	-20° - 90° (auto reverse)
Tilt Speed	0.1° - 74°/s Preset speed: 240°/s
Number of Presets	1024
Patrol	Preset patrol, route patrol, recorded patrol
Home Position	Supported
Audio I/O	Audio cable Input: impedance 1kΩ; amplitude 2V [p-p] Output: impedance 600Ω; amplitude 2V [p-p]
Alarm I/O	2/1
Serial Port	1 RS485
Network	1 RJ45 10M / 100M Base-TX Ethernet
Power	AC 24V ±25%, DC 24V±25%, PoE++ (IEEE 802.3bt) (IEEE802.3bt switch required) Power consumption: 16 - 51W
Dimensions (Ø x H)	Ø270 x 496.7mm (Ø10.6" x 19.6")
Weight	9.69kg (21.4lb)
Working Environment	-40°C - 70°C (-40°F - 158°F), Humidity: ≤95% RH (non-condensing)
Ingress Protection	IP66
Reset Button	Supported

Dimensions

