

IPZ-P6233W-S

2MP 33x Starlight Network PTZ Dome Camera



Accessories
Control
NVR
Network Camera
Video Decoder

- زوم اپتیکال تا 33 برابر بزرگ نمایی
- لوکس نوری پایین
- فوکوس دقیق و سریع

- رزولوشن 2 مگاپیکسل
- Ultra 256, H.265, H.264, MJPEG
- پشتیبانی از 3 استریم تصویر
- OSD قابل تنظیم

- ### قابلیت های کلیدی
- پشتیبانی از پروتکل ONVIF
 - تکنولوژی کنترل دمای هوشمند
 - بدنه ضد ضربه با استاندارد IK10
 - مقاومت در برابر نفوذ آب و گرد و غبار IP67

Specifications

| Sensor | 1/2.8", 2.0 megapixel, progressive scan, CMOS | | | | | | | | | | | | | | | |
|-------------------------|---|-------------|---------------|--------------|---------------|--------------|-----|------|------|----|---|-------|--------|-------|-----|-------|
| Lens | 4.5 - 148.5mm, AF automatic focusing and motorized zoom lens | | | | | | | | | | | | | | | |
| Digital Zoom | 16 | | | | | | | | | | | | | | | |
| Optical Zoom | 33 | | | | | | | | | | | | | | | |
| | <table border="1"> <thead> <tr> <th>Lens (mm)</th> <th>Detect (m)</th> <th>Observe (m)</th> <th>Recognize (m)</th> <th>Identify (m)</th> </tr> </thead> <tbody> <tr> <td>4.5</td> <td>69.8</td> <td>27.9</td> <td>14</td> <td>7</td> </tr> <tr> <td>148.5</td> <td>2094.8</td> <td>837.9</td> <td>419</td> <td>209.5</td> </tr> </tbody> </table> | Lens (mm) | Detect (m) | Observe (m) | Recognize (m) | Identify (m) | 4.5 | 69.8 | 27.9 | 14 | 7 | 148.5 | 2094.8 | 837.9 | 419 | 209.5 |
| Lens (mm) | Detect (m) | Observe (m) | Recognize (m) | Identify (m) | | | | | | | | | | | | |
| 4.5 | 69.8 | 27.9 | 14 | 7 | | | | | | | | | | | | |
| 148.5 | 2094.8 | 837.9 | 419 | 209.5 | | | | | | | | | | | | |
| Angle of View (H) | 62.67° - 2.82° | | | | | | | | | | | | | | | |
| Angle of View (V) | 38.4° - 1.3° | | | | | | | | | | | | | | | |
| Angle of View (O) | 77.1° - 3.3° | | | | | | | | | | | | | | | |
| Shutter | Auto/Manual; shutter time: 1 ~ 1/100000s | | | | | | | | | | | | | | | |
| Minimum Illumination | Colour: 0.001Lux (F1.5, AGC ON) B/W: 0.0001Lux (F1.5, AGC ON) | | | | | | | | | | | | | | | |
| Iris | Auto/Manual; F1.5 ~ F4.0 | | | | | | | | | | | | | | | |
| Day/Night | IR-cut filter with auto switch (ICR) | | | | | | | | | | | | | | | |
| Digital noise reduction | 2D/3D DNR | | | | | | | | | | | | | | | |
| S/N | >52dB | | | | | | | | | | | | | | | |
| Defog | Defog Digital | | | | | | | | | | | | | | | |
| WDR | 120dB | | | | | | | | | | | | | | | |
| Video Compression | Ultra 265, H.265, H.264, MJPEG | | | | | | | | | | | | | | | |
| H.264 code profile | Baseline profile, Main Profile, High Profile | | | | | | | | | | | | | | | |
| Frame Rate | Main Stream: 2MP (1920*1080), Max 30fps; Sub Stream: 2MP (1920*1080), Max 30fps; Third Stream: D1 (720*576), Max 30fps | | | | | | | | | | | | | | | |
| HLC | Supported | | | | | | | | | | | | | | | |
| BLC | Supported | | | | | | | | | | | | | | | |
| EIS | Supported | | | | | | | | | | | | | | | |
| OSD | Up to 8 OSDs | | | | | | | | | | | | | | | |
| Privacy Mask | Up to 24 areas | | | | | | | | | | | | | | | |
| ROI | Up to 8 areas | | | | | | | | | | | | | | | |
| Motion Detection | Up to 4 areas | | | | | | | | | | | | | | | |
| Smart Features | Audio detection, Cross line, intrusion, object left, object removed, people counting, face capture, Auto tracking | | | | | | | | | | | | | | | |

| | |
|------------------------|--|
| General Function | Watermark, IP Address Filtering, Tampering Alarm, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication |
| Audio Compression | .711 |
| Two-way audio | Supported |
| Suppression | Supported |
| Sampling Rate | 8KHZ |
| Edge Storage | Micro SD, up to 256GB |
| Network Storage | ANR |
| Protocols | IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS |
| Compatible Integration | ONVIF (Profile S, Profile G, Profile T), API |
| Pan Range | 360° (endless) |
| Pan Speed | 0.1°/s - 400°/s Preset speed: 400°/s |
| Tilt Range | 1° - 90° |
| Tilt Speed | 0.1° - 240°/s Preset speed: 240°/s |
| Number of Presets | 1024 |
| Patrol | Preset patrol, route patrol, recorded patrol |
| Home Position | Supported |
| Audio I/O | Audio cable 1 Input: impedance 35kΩ; amplitude 2V [p-p] 1 Output: impedance 600Ω; amplitude 2V [p-p] |
| Alarm I/O | 2/1 |
| Serial Port | 1 RS485 |
| Network | 1 RJ45 10M/100M Base-TX Ethernet |
| Video Output | 1 BNC, impedance 75Ω; amplitude 1V [p-p] |
| Power | AC 24V±25%, DC 24V±25%, PoE (IEEE 802.3at) Power consumption: Max 16W |
| Dimensions (Ø x H) | Ø218 x 298mm (Ø8.6" x 11.7") |
| Weight | 4.2kg (9.3lb) |
| Working Environment | -30°C ~ 70°C (-31°F ~ 158°F), Humidity: ≤95% RH (non-condensing) |
| Ingress Protection | IP67 |
| Vandal Resistant | IK10 |
| Reset Button | Supported |

Dimensions

