

IPC-A1A2WH-I200S

2MP 22x Starlight WDR Network IR Bullet Camera



قابلیت های کلیدی

- قابلیت روز و شب
- IR هوشمند تا 200 متر
- کاهنده نویز دیجیتال 3D

- Ultra 265, H.265, H.264, MJPEG
- پشتیبانی از 3 استریم تصویر
- پشتیبانی از ROI
- پشتیبانی از حالت راهرو 9:16
- OSD قابل تنظیم

- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -40 تا +60 درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- پایه قابل تنظیم 3 حالت

Specifications

Sensor	1/1.8", 2.0 megapixel, progressive scan, CMOS				
Lens	6.5 - 143mm, AF automatic focusing and motorized zoom lens				
Optical Zoom	22				
DORI Distance	Lens(mm)	Detect(m)	Observe(m)	Recognize(m)	Identify(m)
	6.5	78	31.2	15.6	7.8
	143	1716	686.4	343.2	171.6
Angle of View (H)	59° - 3°				
Angle of View (V)	34.6° - 1.6°				
Angle of View (D)	72.6° - 3.6°				
Adjustment angle	Pan: 0°-360°		Tilt: 0°-90°		Rotate: 0°-360°
Shutter	Auto/Manual, 1 - 1/100000s				
Minimum Illumination	Colour: 0.0005Lux (F1.5, AGC ON) 0Lux with IR				
Iris	Auto/Manual, F1.5 - F3.4, DC-Iris				
Day/Night	IR-cut filter with auto switch (ICR)				
Digital noise reduction	2D/3D DNR				
S/N	>52dB				
IR Range	up to 200m (656ft) IR range				
Defog	Defog Digital				
WDR	120dB				
Video Compression	Ultra 265, H.265, H.264, MJPEG				
H.264 code profile	Baseline profile, Main Profile, High Profile				
Frame Rate	Main Stream: 2MP (1920*1080), Max 60fps;				
	Sub Stream: 2MP (1920*1080), Max 60fps;				
	Third Stream: D1 (720*576), Max 60fps				
9:16 Corridor Mode	Supported				
ROI	Supported				
HLC	Supported				
BLC	Supported				
OSD	Up to 8 OSDs				
Motion Detection	Up to 4 areas				
Smart Features	Audio detection, Cross line, intrusion, object left, object removed, People Counting, Face Capture				
Privacy Mask	Up to 8 areas				
General Function	Watermark, IP Address Filtering, Tampering Alarm, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication				
Audio Compression	6.711				
Two-way audio	Supported				
Suppression	Supported				
Sampling Rate	8KHZ				
Edge Storage	Micro SD, up to 256GB				
Network Storage	ANR				
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS				
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API				
Audio I/O	Audio cable				
	1 Input: impedance 35kΩ; amplitude 2V [p-p] 1 Output: impedance 600Ω; amplitude 2V [p-p]				
Alarm I/O	2/1				
Serial Port	1 RS485				
Network	1 RJ45 10M/100M Base-TX Ethernet				
Video Output	1 BNC, impedance 75Ω; amplitude 1V [p-p] AC 24V±25%, PoE (IEEE 802.3at)				
Power	Power consumption: Max 21W				
Dimensions (L × W × H)	396.5 × 137 × 112mm (15.6" × 5.4" × 4.4")				
Weight	3.7kg (8.2lb)				
Working Environment	-40°C - 60°C (-40°F - 140°F), Humidity: ≤95% RH (non-condensing)				
Ingress Protection	IP67				
Reset Button	Supported				

Dimensions

