

MODEL: DSP-PG21

PAGING ADAPTER

پیجینگ تحت شبکه



◀ سفارشی‌سازی شده برای بهترین عملکرد در نرم‌افزار نظارت تصویری جنتک

◀ قابلیت اضافه شدن به صورت Unit اختصاصی تحت پروتکل Onvif در نرم‌افزار جنتک

◀ دارای دو عدد رله NO , NC

◀ قابلیت اضافه شدن در Sipelia جنتک

◀ قابلیت اتصال میکروفون

◀ قابلیت مدیریت ورودی و خروجی به صورت کلید

◀ قابلیت اتصال به آمپلی‌فایر

◀ قابلیت اتصال به بلندگو 15 وات

◀ قابلیت ریست سخت‌افزاری

◀ سازگار با انواع نرم‌افزار های نظارت تصویری

◀ POE

Genetec

AVIGILON
MOTOROLA
SOLUTIONSdigiFort
2020 BROCHUREaxxi4next
EXPERIENCE THE NEXT

CISCO

milestone

MODEL: DSP-PG21

PAGING ADAPTER

پیجینگ تحت شبکه

Specification

Audio	
Decoding	OPUS 48 kHz, MP3 44.1 kHz, G.722 ADPCM 16 kHz, G.711 PCMU 8 kHz, G.711 PCMA 8 kHz
Network	
Security	Password protection, IP address filtering, Digest authentication, User access log
Network Protocol	SIP, ONVIF, HTTP, HTTPS, IPv4, TLS, RTSP, RTP, RTCP, DHCP, DNS, NTP, TCP, UDP, IGMP, ICMP, ARP
Network Interface	10/100 Base-TX, RJ45
VoIP	Supports SIP protocol for integration with VoIP systems and SIP/PBX. Support ONVIF protocol for interaction with security systems, integrated with ONVIF VMS/NVR. 2 SIP Accounts, SIP Direct IP Call, RTP Multicast Codecs: OPUS, G722, G711U, G711A.
Amplifier	
Amplifier	15W
General	
Material	Metal
Power Supply	PoE or DC 12V
Interface	2×LAN, 1× MIC input, 1×Headset output, 1×Speaker output, 2× IO Alarm input, 2×Relay
Dimensions	112mm *105mm * 29mm
Weight	250g
Languages	English
Warranty	1 years
Package includes	SIP Paging Adapter Quick Start Guide
Customization	Accept OEM, ODM
Compatibility	Genetec ,Milestone ,Avigilon ,Cisco ,Axxonnext ,Digifort