

سوییچ رک مونت

Model: SW-2456GA-4S-WEB

دارای 24 پورت شبکه POE 1000Mbps

دارای 2 پورت SFP+ , 1000Mbps

سوییچ مدیریتی



ویژگی ها

- ◀ نمایش وضعیت سوییچ از طریق چراغ های روی پنل
- ◀ پشتیبانی از VLAN, QoS
- ◀ دارای خروجی 30 وات به ازای هر پورت
- ◀ ظرفیت سوییچ 56 Gbps
- ◀ 370 W
- ◀ پشتیبانی از 802.1Q VLAN, Port VLAN, QoS - کنترل پهنای باند
- ◀ پشتیبانی از Auto MDI/MDIX
- ◀ پشتیبانی از IEEE802.3x full-duplex flow control and Backpressure half-duplex flow control
- ◀ شناسایی هوشمند ارسال دیتا در کابل شبکه
- ◀ پشتیبانی از عملکرد صرفه جویی در مصرف برق اترنت
- ◀ پشتیبانی از مدیریت ترافیک پورت، نظارت بر عملکرد پورت و محافظت در برابر Loopback
- ◀ محافظت از حملات DDOS

2 سال
گارانتی طلایی
تعویض

Model	SW-2456GA-4S-WEB
Interface	24*10/100/1000Mbps adaptive RJ45 ports 4*1000Mbps SFP ports
Standard	IEEE802.3, IEEE802.3a, IEEE802.1ab, IEEE802.3u, IEEE802.3ab, IEEE802.3z, IEEE802.3x, IEEE802.1q, IEEE802.1p, IEEE802.3af, IEEE802.3at
Network Media(Cable)	10BASE-T: UTP category 3, 4, 5 cable (≤100m) 100BASE-TX: UTP category 5,5e cable (≤100m) 1000BASE-T: UTP category 5e,6 cable(≤100m) 1000BASE-X: indicates the MMF module
LED Indicator	PWR (Orange), LNK/ACT (Green), PoE (Orange)
MAC Address Table	16K, Auto-learning, Auto-update
Jumbo Frame	12KBytes
Packet Buffer	8.4Mbit
Transfer Mode	Store-and-Forward
Switching Capacity	56Gbps
Packet Forward Speed	41.66Mpps
Input Voltage	AC:100-240V,50/60Hz
Total Power Supply	385W
Total Power Supply	370W
PoE Port	Port 1~24
PoE Total Power	30W(Max)
RJ45 PoE Power Supply	1/2(+),3/6(-)
Dimensions(L*W*H)	440*207*44mm
Operating Temperature	0°C ~ 50°C
Storage Temperature	-40 °C ~70°C
Operating Humidity	10% ~ 90% non-condensing
Storage Humidity	5% ~ 90% non-condensing
Surge Protection	Differential mode ±2KV, Common mode ±6KV
Electrostatic Standard	Contact ±6KV , Air ±8KV
MTBF	>50000 hour

Function menu	Functional description	Added
Basic	Login authentication and logout	
	Bilingual (Chinese-English Switching)	
System Settings	Device Info	Hostname
		Device Contact
		Device Location
	IP Settings	
	Web Settings	Web timeout settings
	User Management	Password must contain at least letters&Number length is not less than 6
	Upgrade	Local Upgrade
	Device Management	Reboot
		Restore
Monitoring	Port Statistics	
	Cable Diagnostics	
	Loop Guard	rldp/rlpp/rlcp
	ONVIF Detect	
Switch Settings	Port Settings	Status
		Speed/Duplex/Flow Control
		CCTV
	Port Mirroring	In/Out/All
	Port Isolation	Simple implementation of VLAN reference dump
	Link Aggregation	Static
	Static MAC	
	Filter MAC	
	Search MAC	
	MAC List	Classified display static/dynamic mac address
VLAN Settings	VLAN Member	
	VLAN Settings	Access、Trunk
QOS Settings	Port Rate	
	Storm Control	
	QOS queue setup	
PoE Settings	PoE Basic Settings	Support enabled/disabled PoE port
		Force Power
		PoE Port Limit
	PD Alive	