

Model: DSP-ANPR-H20

دوربین گلوبال شاتر

Lens: Fixed, 16mm

H264,H265,MJPEG

2 MegaPixel



دوربین گلوبال شاتر تحت شبکه

قابلیت رکورد در نرم افزار و رکورد های نظارت تصویری

مناسب برای پلاک خوانی جهت دو لاین

دارای نور رنگی مناسب جهت تشخیص پلاک

دو مگا پیکسل

مناسب برای پلاک خوانی تا سرعت 200 کیلومتر

camera	
Sensor	1/2 Global Shutter SC233A
Min. Illumination	Color: 0.001 Lux @ (F1.4, AGC ON), B/W: 0.0005 Lux @ (F1.4, AGC ON), 0 Lux with IR
Shutter Time	8 us-20000 us
Lens	Fixed, 16mm
Ethernet Interface	1 RJ45 10 M/100 M/self-adaptive Ethernet interfaces
Encoding Mode	H264,265
Encoding Level	baseline,main profile,high profile
Resolution	1080P,2M(1600*1300),UXGA(1600*1200),960P,720P
Frame Rate	(1~30)NTSC,(1~25)PAL
Bitrate	1024~8000
Frame Interval	1~150
Subcode Stream	
Encoding Mode	H264,H265,MJPEG
Encoding Level	baseline,main profile,high profile
Resolution	720P,SVGA(800*600), D1, VGA,CIF
Frame Rate	(1~30)NTSC,(1~25)PAL
Stream Control	Variable Stream or Fixed Stream
Bitrate	32~4000
Frame Interval	1~150
Encoding Format	NTSC,PAL
Application	Outdoor
Power Supply	AC220
Operating Condition	-40°C~70°C
Dimensions (L × W × H)	497.7mm×122.6mm×168.9mm
Weight	3 kg
Material	Shell:aluminum alloy Sun shield:plastic
Ingress Protection	IP66
Warm Light Distance	45 m
API	HTTP API Specification

